



FIG.1

RM 型 / RM Core

型号 TYPE	图例 FIG.	尺寸 Dimensions (mm)						
		A	B	C	D	E	F	G
RM4	1	10.8±0.2	5.2±0.15		3.9+0/-0.2	7.95min	3.5min	
RM5L	1	14.9max	5.2±0.15		4.8±0.2	10.4±0.3	3.15min	
RM6T	1	17.9+0/-0.7	6.2±0.1		6.3+0.1/-0.2	12.4min	4.0min	
RM8BN	1	22.75±0.45	8.2±0.1	10.8±0.2	8.4±0.15	17.3±0.3	5.5±0.15	7.35±0.15
RM10/18.6AK	1	27.8±0.65	9.3±0.1	13.25±0.25	10.7±0.2	21.4min	6.45±0.2	8.35±0.15
RM14AI	1	42.2+0/-1.2	15.05±0.2	19+0.2/-0.6	15.0+0/-0.5	29.0+1.0/-0	10.55±0.2	13.7±0.2

H	I	C1	Ae	Le	Amin	Ve	AL(±25%)				重量 g /PRS
							TS5	TS7	TS10镜面	TS13镜面	
9.6±0.2		1.62	13.90	22.50		313.00	1900	2150	2900 min	3200 min	1.63
12.3+0/-0.6		1.05	23.13	24.18	18.10	559.40	3000	3500	4500 min	5200 min	2.90
14.7+0/-0.6		0.88	34.71	30.51	30.68	1059.10	4100	4800	6000 min	7000 min	5.50
19.5+0/-0.8	9.8min	0.67	59.82	40.35	55.42	2413.40	6000	7200	8400 min	9800 min	12.50
24.15±0.55	13min	0.54	88.67	48.17	86.90	4271.20	8000	9700	11000 min	13000 min	22.20
34.8+0/-1.3	17.0min	0.38	194.09	73.94	170.87	14350.20	13000	16000	17500 min	21000 min	74.60